

USAlert WatchDog™

M and Mx series pagers

M1, MX1, M2, MX2, M5 and MX5

USAlert's continuation of
advanced paging products and
service excellence™

The **WatchDog M series:**

Very simple, very loud and very rugged.

The M1 single channel or M2 dual channel operation or the M5 five channel pager. Source alert text messaging and message time stamping.

Tone alert, vibrate alert or simultaneous tone and vibrate. The WatchDog also has a true alphanumeric display making operational changes simple and fast. The M5 can operate on a single channel or any two of five menu selectable channel frequencies.

The **WatchDog MX series:**

The same rugged design as the M series but with voice memory. The MX pagers voice memory allows easy replay and complete message control. Forward and reverse message select and replay.



Synthesized and Five Channel

A man's best friend is his dog
a fireman's best friend is his **WatchDog™**

USAlert, LLC
164 West Royal Palm Road
Boca Raton, Florida, 33432-3830
Phone: 561 394 9969

Sales: Robert O'Sullivan
Email: info@usalertllc.com
Fax: 561 394 9986
Web: www.usalertllc.com

WATCHDOG™

FEATURES AND SPECIFICATIONS

M Features:

- Two Tone Decoding Format
- 15 Addresses Per Channel
- Optional 2nd Channel
- Tone Alert, Vibrate Alert or Tone-Vib alert
- On / Off Volume Control
- Alphanumeric display
- Quick Monitor Control
- Audio Lock On
- Multi Function Scan
 - Channel Scan
 - Selective Call Scan
 - Priority Scan
- Low Battery Alert
- Wideband and Narrowband Models

M continued

- Programmable Text Alert Messaging
- Alert Time Stamping
- Forward Message Playback Select
- Reverse Message Playback Select
- Delete Message
- Delete all Messages
- Message Protect
- 3 Bar Graphic Battery Level Indication
- Menu selectable options

MX same as the M series plus

- 4 minutes voice memory

Band	VHF	UHF
Frequency Range MHz	138 - 174	406 - 512
Frequency Stability	+/- 0.0010%	+/- 0.0005%
Channel Spacing	15 KHz / 30 KHz	12.5 KHz / 25 KHz
Sensitivity / Alerting	4.0 uV/m	3.5 uV/m
Sensitivity / 12dn SINAD	9uV/m	10uV/m
Adjacent Channel Selectivity	65dB	65dB
Spurious & Image Rejection	>55dB	>55dB
Audio Output Linear	> 750 mw	> 750 mw
Alert	96dB SPL @ 12"	96dB SPL @ 12"
Voice	98dB SPL @ 12"	98dB SPL @ 12"
Audio Distortion	< 2%	< 2%
Battery Life Ni-Cd	6 days	6 days
Battery Life Alkaline	8 days	8 days
Dimensions	2.95" X 1.9" X0.86"	2.95" X 1.9" X0.86"
Weight	105g	105g